


Tow & Recovery

Towmans™ Certified
Lighting & Accessories



WHELEN®
TRUSTED TO PERFORM™

Table Of Contents

New Lightbars	Page 3
Lightbars	Page 4-5
Dash & Deck	Page 6
PAR-36 & PAR-46	Page 7
Lighthoods	Page 8-14
Bacons	Page 15
Illumination	Page 16-17
Traffic Advisor™	Page 18
Light Arrays	Page 19
Interior Lights	Page 19

Towman's™ Justice® Lightbars



JF01AAAA

- JF01AAAA has OEM "U" bracket mounting with plug & play harness
- JF02AAAA has OEM "U" bracket mounting with plug & play harness plus identification light



OEM "U" Bracket Mounting



OEM Plug & Play Harness



Red LED Identification Light
(JF2AAAA only)

Towman's™ Series Lightbars

Towman's Freedom™ IV Series



F40BAAAA

Towman's Liberty™ II Series

PROCLERA
SILICONE OPTICS



IW0BAAAA

Towman's Justice® Competitor Series



JF0BAAAA

Towman's Century™ Series



CW0BAAAA

Towman's™ Series Lightbars

FEATURES

- SAE Class 1 Certified
- Liberty™ II models feature Whelen's all-new Proclera® Silicone Optics for increased clarity (available in work lights)
- Front/rear warning lights are separately controlled
- Includes rear facing LED brake/tail/turn signals
- Three adjustable slide bolt mount
- Many options available, consult price list and/or WeCad™ software
- 12 VDC
- Five year warranty

Model	Series	Length	Size	Lighting	Inboard Warning Lights	FPM	Base	Lenses
F40BAAAA	Freedom™ IV	60" (154cm)	3-3/4" (94mm) H x 12-1/2" (318mm) D	4 Linear-LED® corners, 2 Super-LED® work lights, 2 LED brake/tail/turn lights	8 Amber Economy LED (2 front/6 rear)	12 Scan- Lock™	Extruded aluminum	Clear
IW0BAAAA	Liberty II		2-1/2" (64mm) H x 11-5/16" (287mm) D		6 Amber Linear-LED (2 front/4 rear)	WeCan®		
CW0BAAAA	Century™		2-1/4" (57mm) H x 12" (304mm) D		4 Amber Linear-LED (2 front/2 rear)	52 Scan- Lock	Extruded aluminum I-Beam	Color lenses standard
JF0TAAAA	Justice®	62-3/8" (158cm)	2-1/4" (57mm) H x 12" (304mm) D		Optional*			
JF0BAAAA					6 Amber CON3™*			
JF0DAAAA					Amber CON3* & Traffic Advisor™			
JF01AAAA					6 Amber CON3 & B/T/T			
JF02AAAA				6 Amber CON3 & B/T/T				
JF0FAAAA				No work lights	16 Amber CON3 & B/T/T			

* Note: Can also add options.

OPTIONS

Liberty II Options	
Model	Description
IWDLA	Long 6 Super-LED lighthead, Amber
IWDSA	Short 3 Super-LED lighthead, Amber

Century Options	
Model	Description
CEDLXA	One LIN12™, Amber
CDT6A	One TIR6, Amber

Freedom IV Options	
Model	Description
F4EDLA	One single color long economy DYAD™ Lighthead, Amber

Justice Options	
Model	Description
JDC*	One CON3

Dash & Deck

Avenger™ II Series



- SAE Class 1 Certified
- Single or dual Linear Super-LED® interior light
- Available in SOLO™ (single color), and DUO™ (two color)
- Snap-on polycarbonate hood
- Mounts via swivel/bail bracket with three suction cups
- Single: 1-3/4" (44mm) H x 4-1/2" (114mm) D x 6-1/2" (165mm) L
- Dual: 1-3/4" (44mm) H x 4-1/2" (114mm) D x 10-1/4" (260mm) L



Model	Series	Technology	Lamp	Colors
AVC11*	Cigar Plug	Super-LED	Single	Amber, Blue, or White
AVC21**			Dual	Amber, Blue, or White
AVW11*	2-Wire Pigtail		Single	Amber, Blue, or White
AVW21*			Dual	Amber, Blue, or White
AVC12#	Cigar Plug		Single	Amber/White, Blue/Amber
AVC22FF			Dual	Two Amber/White
AVC22MM		Two Blue/Amber		

Replace symbol * in model number with letter indicating desired color: A=Amber, B=Blue, R=Red, C=White
 Replace symbol # in model number with letter indicating desired color: D=Red/White, E=Blue/White,
 F=Amber/White, J=Red/Blue, M=Blue/Amber

SpitFire ION™

- SAE Class 1 Certified
- ION Super-LED interior dash and deck light
- Fully encapsulated for moisture, vibration, and corrosion resistance
- Includes universal bracket, windshield suction cup mount
- Includes integral hood and 10' cord with cigar plug, On/Off switch with LED "On" indicator, and Scan-Lock™ pattern control switch
- Size: 1-5/8" (41mm) H x 3-3/8" (86mm) D x 5-1/8" (130mm) W



Model	Series	Technology	Lamp
SFIONA	Cigar Plug	Super-LED	Single

SlimLighter™

- SAE Class 1 Certified
- TIR6™ Super-LED interior light
- Swivel bracket for permanent or suction cup mounting included
- Includes built-in pattern selection button, 10' straight cord with cigar plug and On/Off switch with LED "On" indicator
- Size: 1-5/8" (41mm) H x 1-3/16" (45.5mm) D x 16-3/8" (416mm) W



Model	Series	Technology
SLPMMAA	Cigar Plug	TIR6 Super-LED

Slim-Miser™

- 5mm LEDs for interior use
- Includes 10' straight cord with cigar plug, On/Off switch with LED "On" indicator
- Swivel mount with 3 suction cups securely hold dash light to windshield minimizing flashback
- Size: 1-5/8" (41mm) H x 2-3/4" (70mm) D x 12-7/8" (326mm) L



Model	Series	Technology
SMLLAA	Cigar Plug	5mm LED

PAR-36 & PAR-46

- Available in floodlight or spotlight models
- Black cast aluminum housing
- Super-LED® with low current draw
- Stainless steel bracket and hardware included

Model	Series	Lighting	VDC
PFBP12	PAR-36	Flood	12
PFBP12C			
PFBS12			
PFBS12C			
PFBS6S			
PSBP12		Spot	
PSBP12C		Pedestal	
PSBS12		Stud	
PFBS12C			
PFBS12S			



Replacement Lamps

- Drop-in replacements for outdated Halogen lamps

Model	Series	Lighting	VDC
P36SLC	PAR-36	Spot/flood	12/24
P46SLC	PAR-46	2° Spotlight	12

P36SLC



Handheld Spot/ Floodlights

- 90# pull magnet mount, with 8' coiled cord and cigar plug
- Built-in push-button On/Off switch

Model	Series	Lighting	VDC
P36HHS	PAR-36	Spot/flood	12/24
P46HHS	PAR-46	Spotlight	12



Rubber Housing

- Rubber stud/swivel housing with stainless steel bracket and hardware

Model	Series	Lighting	VDC
P36SLCHG	PAR-36	Spot/flood	12/24
P46SLCHG	PAR-46	Spotlight	12



Lightheads



MCRNSA

Micron™ Series

- SAE Class 1 Certified
- Linear Super-LED®
- 25 Scan-Lock™ flash patterns
- Surface mount, includes Black flange
- Includes 6" pigtail
- Size: 7/8" (23mm) H x 7/8" (23mm) D x 4" (102mm) L

Model: MCRNSA



IONA

ION™ Series

- SAE Class 1 Certified
- Directional or wide-angle light spread optic
- 25 Scan-Lock flash patterns
- Surface mount model includes Black flange
- Wide-angle model is universal mount
- Universal mount model includes combination permanent/pedestal, clip, edge mounts, double sided tape. Choice of Black or White housings
- Optional pedestal, bail bracket and grommet mounts are available
- Includes 6" pigtail
- Surface Mount Size: 1-3/4" (43mm) H x 5-7/8" (150mm) W x 1-1/8" (29mm) D
- Wide-Angle and Universal Mount Size: 1" (25mm) H x 4" (102mm) W x 1-5/16" (33mm) D

Models: IONSMA, IONA, WIONA



TLIA

ION T-Series™

- SAE Class 1 Certified
- Extreme low profile, ultra thin lighthead
- 25 Scan-Lock flash patterns
- Surface mounts with two screws
- Includes Black flange
- Includes 4 wire 6" pigtail
- Size: 1-1/2" (38mm) H x 1/2" (13mm) D x 5" (127mm) L

Model: TLIA



TLMIA

ION Mini T-Series

- SAE Class 1 Certified
- Linear Super-LED optics
- 25 Scan-Lock flash patterns
- Synchronize to other Whelen sync products
- Easily surface mounts with two screws
- Includes Black flange and a 4-wire 6" pigtail
- Rated IP67 for dust and water resistance
- 12 VDC
- Size: 1.50" (3.81cm) H x .50" (1.27cm) D x 3.34" (8.48cm) L

MODEL: TLMIA

Lightheads



IONSV1AC

ION™ V-Series™

- SAE Class 1 Certified
 - 3-in-1 180° wide-angle warning, illumination, and puddle light
 - 25 Scan-Lock™ flash patterns
 - Includes Chrome flange
 - Surface mount, includes 6" pigtail
 - Optional bail/swivel bracket in Black or White, pedestal mount in Black or Chrome and rubber grommet
 - Size: 1-3/4" (43mm) H x 5-7/8" (150mm) W x 1-7/8" (48mm) D
- Model:** IONSV1AC



I2F

ION DUO™ Series

- SAE Class 1 Certified
 - Directional light spread optic
 - Independent control of color one and color two
 - 64 Scan-Lock flash patterns
 - Universal mount
 - Includes combination permanent/pedestal, clip, edge mounts, double sided tape. Choice of Black or White housings
 - Optional pedestal, bail bracket, and grommet mounts are available
 - Includes 6" pigtail
 - Size: 1" (25mm) H x 1-1/4" (32mm) D x 4" (101mm) L
- Model:** I2F



V23ATPB with V23PEDB

V23™ V-Series

- SAE Class 1 Certified
 - 3-in-1 combination 180° wide-angle warning, flood/alley, and ground illumination
 - 26 Scan-Lock flash patterns
 - Built-in flasher
 - Includes surface mount flange in Chrome or Black
 - Optional pedestal mount and angled flange for mounting on a curved body panel of any vehicle
 - Size: 2-11/16" (68mm) H x 1-1/2" (38mm) D x 4-1/4" (109mm) L
- Models:** V23ATPB, V23ATBC

Lightheads



OSA00FCR

OS Series

- Tiny oval encapsulated interior/exterior LED lighthouse
- One flash pattern and built-in flasher
- Surface mount, includes Chrome flange
- Includes 6" pigtail
- Size: 1" (25mm) H x 1/2" (13mm) D x 1-1/2" (38mm) L

Model: OSA00FCR



VTX609A



VTX609C

Vertex™ Series

- Omni-directional lighthouse
- Produces light in a hemispheric pattern
- 25 Scan-Lock™ flash patterns
- Designed to mount in composite style headlight or taillight, or surface mount to exterior surfaces with flange mount option
- Includes 9' cable
- Size: 1" (26mm) H x 1-5/8" (41mm) Dia.

Models: VTX609A, VTX609C



RSA02ZCR



RSA03ZCR

TIR3™ / LIN3™

- SAE Class 1 Certified
- TIR3 optic is directional, LIN3 optic produces a 180° light spread
- 25 Scan-Lock flash patterns
- Surface mount, includes Black flange
- Includes 6" pigtail
- Size: 1-1/8" (28mm) H x 3-1/2" (89mm) L x 1-1/4" (32mm) D with flange

Models: RSA02ZCR, RSA03ZCR



LINZ6A

LINZ6™

- SAE Class 1 Certified
- Sub-compact, with wide-angle light spread
- 69 Scan-Lock flash patterns
- Surface mount, includes Black flange
- Low current draw, fully encapsulated
- Size: 2" (50mm) H x 4" (102mm) W x 1-5/8" (40mm) D

Model: LINZ6A



RBKT18

Brackets

- Rear bed rail mount bracket, comes in pairs. Lighthouse sold separately

Model	Option Description
RBKT12	2013-2016 Ford F-250/350/450/550 (Above)
RBKT14	2014-2018 Chevy Silverado (Above)
RBKT18	2015-2018 Ford F-150 (Above)
RBKT19	2015-2018 Ford F-150 (Below)

Lightheads

2GA00FAR



5GA00FAR

2G & 5G Series

- 15 Scan-Lock™ flash patterns
- Vinyl grommet mount lighthouse
- Compatible with competitive 4" and 6" lights and their mounting accessories
- Includes 12" pigtail
- 2G Size: 5-1/2" (140mm) Dia. x 1-1/4" (31mm) D (with grommet)
- 5G Size: 3-3/16" (81mm) H x 7-7/16" (189mm) W x 1-1/4" (32mm) (with grommet)

Models: 2GA00FAR, 5GA00FAR, 5GC00WCR
Option: 2GFLANGC

3SA00FAR



3" Round

- 3 Super-LED® diodes
- 160 FPM
- Surface mount, aluminum housing
- Includes 6" pigtail
- Size: 3" (76mm) Dia.

Model: 3SA00FAR

2FA00ZAR



2EA00ZAR

4" Round

- SAE Class 1 Certified
- 25 Scan-Lock flash patterns
- Includes 6" pigtail
- Size: 4-1/4" (108mm) Dia.

Flat Lens

- TIR6™ Super-LED with synchronize feature
- Surface mount


Model: 2FA00ZAR

Extended Lens

- Linear6™ Super-LED with synchronize feature
- Requires additional mounting

Model: 2EA00ZAR

40AA5SAR



40AA2ZAR

400 Series

- SAE Class 1 Certified
- Linear Super-LED available in single or dual level warning
- Single level model has 25 Scan-Lock flash patterns
- Dual level model requires an external flasher
- Single level model is surface mount
- Dual level model requires additional mounting
- Includes 6" pigtail
- Single Level Size: 3-3/16" (77mm) H x 1-3/8" (34mm) D x 4-15/16" (124mm) L
- Dual Level Size: 3-3/16" (77mm) H x 2" (50mm) D x 4-15/16" (124mm) L

Models: 40AA2ZAR, 40AA5SAR



Lighthoods



50A03ZAR



50A02ZAR

500 Series

- SAE Class 1 Certified
- Available with Linear Super-LED® or TIR6™ Super-LED optics
- 25 Scan-Lock™ flash patterns
- Requires additional mounting
- Includes 6" pigtail
- Linear Super-LED Size: 1-5/8" (41mm) H x 1-3/4" (44mm) D x 5" (127mm) L
- TIR6 Super-LED Size: 1-5/8" (41mm) H x 1-3/8" (35mm) D x 5" (127mm) L

Models: 50A02ZAR, 50A03ZAR



5V1A

500 V-Series™

- SAE Class 1 Certified
- 25 Scan-Lock flash patterns
- Requires optional mounting
- Includes 6" pigtail
- Size: 2-1/8" (54mm) H x 1-5/8" (42mm) D x 5-3/8" (137mm) L

Model: 5V3A

- 3-in-1 combination 180° wide-angle warning, flood/alley, and ground illumination

Model: 5V1A


- Single color combination 180° and TIR directional warning light



60A02FAR



70A02FAR



90AA5FAR

600, 700, & 900 Series

- SAE Class 1 Certified
- Linear Super-LED
- 14 Scan-Lock flash patterns
- Surface mount
- Includes 6" pigtail
- 600 Series Size: 4-1/8" (105mm) H x 6-1/2" (165mm) W
- 700 Series Size: 3-1/16" (78mm) H x 7-1/4" (184mm) W
- 900 Series Size: 7-1/8" (181mm) H x 9-1/8" (232mm) W

Models: 60A02FAR, 70A02FAR, 90AA5FAR



6RBAC

600 Series Rota-Beam™

- SAE Class 1 Certified
- Solid-state "rotating" technology simulates the appearance of a rotating lighthouse without any moving parts or motors
- 14 Scan-Lock flash patterns
- Surface mount
- Includes 6" pigtail
- Size: 4-3/16" (106mm) H x 3-7/16" (87mm) D x 6-9/16" (167mm) L

Model: 6RBAC

Lightheads

M Series

- SAE Class 1 Certified
- Patented Linear-LED® designed reflector assembly
- Clear or color lens
- Multiple Scan-Lock™ flash patterns
- Surface mount



M2A

M2 Series

- Size: 2-1/2" (64mm) H x 4" (102mm) W x 1" (24mm) D
- Models:** M2A, M2AC



M4A

M4 Series

- Size: 3-3/8" (86mm) H x 5-1/2" (138mm) W x 1-3/8" (35mm) D

Models: M4A, M4AC



M6A



M6AC



M6V2A

M6 Series

- Size: 4-5/16" (109mm) H x 6-3/4" (170mm) W x 1-3/8" (35mm) D

Models: M6A, M6AC, M6V2A



M7A

M7 Series

- Size: 3-3/8" (86mm) H x 7-5/8" (194mm) W x 1-3/8" (35mm) D

Models: M7A, M7AC



M9A

M9 Series

- Size: 6-1/2" (165mm) H x 10-3/8" (263mm) W x 1-3/8" (35mm) D

Models: M9A, M9AC



M9LZC

M9 Scenelight

- Certified to meet KKK-1822F requirements
- Surface mount
- Draws 6 amps and produces 6500 lumens
- Size: 6-1/2" (165mm) H x 10-3/8" (263mm) W x 1-3/8" (35mm) D

Model: M9LZC



M6FCV2

M6FCV3

M6FCV4

M6FCV2

- Chrome flange, two light, vertical, lightheads purchased separately
- Size: 10-2/5" (264mm) H x 7-1/100" (178mm) W x 1-5/9" (39mm) D

M6FCV3

- Chrome flange, three light, vertical, lightheads purchased separately
- Size: 14-9/20" (368mm) H x 7-1/100" (178mm) W x 1-5/9" (39mm) D

M6FCV4

- Chrome flange, four light, vertical, lightheads purchased separately
- Size: 18-13/25" (471mm) H x 7-1/100" (178mm) W x 1-5/9" (39mm) D

Beacons

L31 Series Super-LED®

- SAE Class 1 Certified
- UV coated dome
- Powder-coated cast aluminum base
- 100% solid-state
- Conformal coated electronics
- Full reverse polarity protection
- Hard-coated domes minimize environmental damage from sand, sun, salt, and road chemicals
- Available in permanent, magnetic, or magnetic/suction mount models
- Rated for thousands of hours of use
- 12 VDC
- Size: 4" (102mm) H x 7-3/16" (182mm) W

Model: L31HAF



L31HAF

L32 Series Super-LED

- SAE Class 1 Certified
- UV coated dome
- Powder-coated cast aluminum base
- 100% solid-state
- Conformal coated electronics
- Full reverse polarity protection
- Hard-coated domes minimize environmental damage from sand, sun, salt, and road chemicals
- Available in permanent, magnetic, or magnetic/suction mount models
- Rated for thousands of hours of use
- Size: 2-5/8" (67mm) H x 7-3/16" (182mm) W

Model: L32LAF



L32LAF

Illumination

Pioneer™ Series

- Injection molded polycarbonate lenses are impact resistant and hard-coated
- Die-cast aluminum powder coated housing in Black or White
- 100% solid-state electronics are instant On/Off
- Correlated Color Temperature (CCT) of 5,700° Kelvin simulates bright midday light
- Models emit zero EMC radiation, will not interfere with portable communication devices and meets CISPR25 Class 5 levels



NP6BB

NP3BW

Pioneer Nano™ Series

- Three or six diode models
- 8° spotlight pattern, standard. Includes additional 40° x 20° floodlight lens
- Optic lens changes via four screws
- Powder coated stainless steel bail bracket with 3/8" stud carriage bolt mount
- Size 3 Diode: 3-1/2" (89mm) W x 2-1/4" (57mm) H x 1-3/4" (44mm) D
- Size 6 Diode: 3-1/2" (89mm) W x 3" (76mm) H x 1-3/4" (44mm) D

Models: NP3BW, NP6BB



MPBB

Pioneer Micro™ Series

- 8° spotlight pattern comes standard. Includes three additional optic lenses for a light pattern choice of:
 - 90° x 20° wide flood
 - 40° x 20° flood
 - 40° x 8° horizontal flood
- Optic lens changes via four screws
- Powder coated stainless steel bail bracket with 3/8" stud carriage bolt mount
- Size: 4-1/4" (108mm) H x 4-3/4" (121mm) W x 2-13/16" (71mm) D

Models: MPBW, MPBB



PCH2

PCH1

Pioneer & Pioneer Plus™ Series

- Single, Dual, and Max Pioneer Plus scene/work/flood-lights/spotlights
- Requires optional mounting
- Increase clarity with Whelen's all-new, patent pending Proclera™ Silicone Optics for spot/flood lights
- Single Size: 4-1/4" (108mm) H x 8-3/16" (208mm) W x 3" (76mm) D
- Dual Size: 4-1/4" (108mm) H x 14-1/16" (357mm) W x 3" (76mm) D
- Max Size: 6-11/16" (170mm) H x 14-1/16" (357mm) W x 3" (76mm) D
- Please consult current price list for models and options



PCPSM1C

PCPSM2C

Pioneer Plus Surface Mount Series

- Combination spot/flood optic design
- Single or dual panel models
- Single Size: 6-3/8" (162mm) H x 1-3/4" (44mm) D x 9" (228mm) L
- Dual Size: 6-3/8" (162mm) H x 1-3/4" (44mm) D x 16-1/4" (412mm) L

Models: PCPSM1B, PCPSM1C, PCPSM2B, PCPSM2C

Illumination



PSL2BB

PSL1BB

Pioneer SlimLine™ Series

- Single Lamp Models - 8° spotlight pattern comes standard. Includes additional 40° x 20° flood lens
- Dual Lamp Models - 8° spotlight pattern comes standard.
- Includes two additional optic lenses for a light pattern choice of dual 40° x 20° flood or 8° spot and 40° x 20° flood
- Mounts via powder coated stainless steel bail bracket or pedestal/swivel mount
- Single Bail/Stud Size: 3-3/4" (82mm) H x 2-1/8" (55mm) D x 6-7/8" (175mm) W
- Dual Bail/Stud Size: 3-1/4" (83mm) H x 2-3/4" (70mm) D x 2-11/16" (322mm) W
- Single Pedestal/Swivel Size: 3-1/4" (83mm) H x 2-3/4" (70mm) D x 7-1/16" (179mm) W

Models: PSL1BB, PSL2BB, PSL1P



PELCC

Perimeter Enhancement Light

- White light is projected downward at a 40° angle to illuminate a large area
- Six diode Super-LED® module in polycarbonate Chrome or Black housing
- Mounts to vertical surfaces and may be mounted inverted
- Molded rubber gasket protects body panels
- Supplied with 6" pigtail connector (requires customer supplied switching)
- Size: 1" (25mm) H x 1-3/8" (35mm) D x 11-1/2" (292mm) L

Models: PELCC, PELCB



Poles, Folding Tripods, & Ground Tripods

- 57" poles, 3 sizes of folding tripod, and ground tripod options
- Please consult current price list for models and options



OSC00FCR



OSC0EDCR

OS Series

- Fully encapsulated for moisture, vibration, and corrosion resistance
- Hard-coated lenses resist environmental damage from sand, sun, salt, and road chemicals
- Surface mount, includes Chrome flange
- OSC0EDCR, OSC00FCR: 1" (25mm) H x 1/2" (13mm) D x 1-1/2" (38mm) L
- OAC0EDCR: 1" (25mm) H x 7/8" (21mm) D x 1-7/8" (48mm) L

Models: OSC0EDCR, OSC00FCR, OAC0EDCR

Traffic Advisor™

- Front-loaded Super-LED® modules
- Built-in left arrow, right arrow, split arrow, and warning functions
- Black powder coated aluminum extrusion
- Extrusion design allows slide bolt mounting via top, rear, or bottom channel

TAC815, TAC830, TAC850

- 8 Super-LED modules
- Control head may be permanently mounted or temporary mounted by hook-and loop tape
- Control head features an auxiliary control for a device up to 6A
- Select 15, 30, or 50 feet of cable

TACF85

- 8 CON3™ Super-LED modules
- Control head includes remote flash control and end lamp enable/disable feature

TANF85

- 8 Linear Super-LED modules
- Control head includes remote flash control and end lamp enable/disable feature



TAC815



TACF85



TANF85

Light Arrays & Interior Lights



Dominator™ & Dominator Plus™

- SAE Class 1 Certified
 - TIR3™ (3-diode) or LINZ6™ (6-diode) Super-LED® modules
 - Multiple Scan-Lock™ flash patterns
 - Extruded aluminum Black powder coated housing
 - Slide bolt mount
 - Sizes: 7" (178mm) L, 14" (365mm) L
- Models:** D2AA, D4AAAA, DP2AA, DP4AAAA



Tracer™ Series


- SAE Class 1 Certified
- Available in SOLO™ (single color) and DUO™ (two color interleaved) modules
- Lightheades are daisy-chained together in lengths from 1 to 6 modules using the provided extrusion
- 30 Scan-Lock flash patterns
- SOLO models include Traffic-Advisor™
- DUO models feature steady override, such as White steady-burn
- DUO models can be synced to other Whelen sync products
- Cruise light control includes seven adjustable intensity levels
- Easily serviceable clamshell design
- Mounts easily via slide bolt with vehicle specific brackets or universal "L" brackets
- Includes 15' cable with fully encapsulated in-line lamp driver
- IP67 rated for dust and water resistance
- 12 VDC, 0.5 amps peak per module
- Size, single module: .75" (19mm) H x 1.75" (44.45mm) D x 12.5" (317.5mm) L

SOLO	
TCRHS1	1 Lamp Housing
TCRHS2	2 Lamp Housing
TCRHS3	3 Lamp Housing
TCRHS4	4 Lamp Housing
TCRHS5	5 Lamp Housing
TCRHS6	6 Lamp Housing
TCRL*	SOLO Lighthead

DUO	
TCRHD1	1 Lamp Housing
TCRHD2	2 Lamp Housing
TCRHD3	3 Lamp Housing
TCRHD4	4 Lamp Housing
TCRHD5	5 Lamp Housing
TCRHD6	6 Lamp Housing
TCRL**	DUO Lighthead

OPTION	
TCRLBKT	1 "L" bracket and hardware, order one more bracket than number of lamps

Replace symbol * in model number with letter indicating color desired: A = Amber, B = Blue, R = Red, C = White



Fluorent Plus™ Tube Lighting

- 120° Super-LED light assemblies
 - Includes "C" clips for snap-in mounting and "P" clips for fixed mounting
 - Redesigned interlocking PC board and connector places provide vibration resistance
 - Designed for interior or exterior applications
 - Sizes: 5/8" (16mm) H x 9" (228mm), 18" (457mm), 27" (686mm), 36" (914mm), 45" (1143mm), 54" (1371mm), 63" (1600mm) L
- Models:** F09PC, F18PC, F27PC, F36PC, F45PC, F54PC, F63PC



51 Winthrop Road
Chester, CT 06412-0684
860-526-9504
www.whelen.com

ISO 9001 Registered QMS

Distributed by:

WhelenENG



Whelen Engineering reserves the right to upgrade and improve products without notice.
© 2018 Whelen Engineering Company, Inc. Printed in U.S.A.
NASCAR® is a registered trademark of the National Association for Stock Car Auto Racing, Inc.
Code No. 12098Q - 10/01/18



OFFICIAL WARNING LIGHTS OF NASCAR